

**BOLT-TOGETHER
SPECIALTY WHEELS**



**BOLT-TOGETHER
SPECIALTY
WHEELS**


ACCURIDE
WHEELS

ACCURIDE 5° BOLT-TOGETHER SPECIALTY STEEL WHEELS



Hub-Piloted Single-Mounting Two-Piece Flange Nut

10-Hole, 335mm Bolt Circle, 281mm Bore




Item	Wheel Size	Part Number	Wheel Inset	Recommended Valve	O-Ring P/N	Approx Wt. (lbs)	Maximum Load & Infl. (lbs) - (psi)
1	20 x 10.00	29610	6.00"	TR-510	36757	146	12125 - 90
2	20 x 10.00	29729	4.50"	*	50184	162	14000 - 105
3	21 x 18.00	29740	2.75"	Haltec ACC-001	32223	198	12250 - 85
4	20 x 10.00	29741 ⁽²⁾	6.25"	*	50184	168	12500 - 92
5	20 x 10.00	29850	6.34"	*	36757	174	10000 - 110
6	20 x 10.00	29857	4.72"	Haltec ACC-001	50184	167	13000 - 105
7	20 x 10.00	29911	5.00"	TR-510	**	162	13230 - 85
8	20 x 10.00	29914	0.00"	*	32262	134	9000 - 85
9	20 x 10.00	29922	1.00"	TR-510	**	161	14300 - 116
10	21 x 18.00	29923	2.36"	Haltec ACC-001	32223	198	13200 - 80
11	20 x 10.00	50194	2.38"	*	50184	156	13000 - 110
12	20 x 10.00	50257	4.50"	*	50184	166	11000 - 105



Hub-Piloted Single-Mounting Two-Piece Flange Nut

10-Hole, 285.75mm Bolt Circle, 220mm Bore




Item	Wheel Size	Part Number	Wheel Inset	Recommended Valve	O-Ring P/N	Approx Wt. (lbs)	Maximum Load & Infl. (lbs) - (psi)
13	20 x 10.00	50082 ⁽¹⁾	4.72"	*	**	174	9370 - 95



Stud-Piloted Single-Mounting Double Cap Nut

10-Hole, 11¼" Bolt Circle, 8.72" Bore



Item	Wheel Size	Part Number	Wheel Inset	Recommended Valve	O-Ring P/N	Approx Wt. (lbs)	Maximum Load & Infl. (lbs) - (psi)
14	20 x 10.00	29737	2.38"	*	50184	160	13000 - 105
15	20 x 10.00	29748 ⁽¹⁾	4.75"	*	32190	125	9000 - 85



*Customer supplied valve



**Contact Accuride Field Engineering for details at 1-800-869-2275

⁽¹⁾Contact Accuride Sales Department for availability and minimum quantities at 1-800-626-7096

⁽²⁾ 281.74mm Bore

ACCURIDE 5° BOLT-TOGETHER SPECIALTY ALUMINUM WHEELS

	<p>Hub-Piloted Single-Mounting Two-Piece Flange Nut</p> <p>10-Hole, 335mm Bolt Circle, 281mm Bore</p>						
Item	Wheel Size	Part Number	Wheel Inset	Recommended Valve	O-Ring P/N	Approx Wt. (lbs)	Maximum Load & Infl. (lbs) - (psi)
1	20 x 10.00	40048	4.02"	*	100002	85	12300 - 120

	<p>Hub-Piloted Single-Mounting Two-Piece Flange Nut</p> <p>10-Hole, 285.75mm Bolt Circle, 220mm Bore</p>						
Item	Wheel Size	Part Number	Wheel Inset	Recommended Valve	O-Ring P/N	Approx Wt. (lbs)	Maximum Load & Infl. (lbs) - (psi)
2	20 x 10.00	40082	4.02"	*	100002	87	10000 - 86

*Customer supplied valve.

HUB-PILOTTED TUBELESS & TUBE-TYPE WHEELS
 STUD-PILOTTED TUBELESS & TUBE-TYPE WHEELS
 DEMOUNTABLE RIMS & COMPONENTS
 DUPLEX DISC® WHEELS/DUPLEX® DEMOUNTABLE RIMS
 LIGHT TRUCK WHEELS
 BOLT-TOGETHER SPECIALTY WHEELS
 GENERAL INFORMATION