

Accuride and KIC Aluminum Wheel Cross Reference

ALUMINUM HUB-PILOTED 15° TUBELESS WHEELS

Wheel Size (Dia. x Width)	KIC Part Number	Polish Option	Hand Holes	Wheel Offset	Disc Thickness	Bolt Hole (#, Diameter)	Weight (lbs.)	Valve Stem	Max Load Rating (lbs.) - (psi)	Accuride Part Number	Alcoa Part Number	Accuride Weight (lbs.)
17.5 x 6.75	AH17501-8P	Polish both Sides (Valve stem installed)	8	5.55"	0.83"	8 - 275mm	29	TR544D	5600 - 125	40171SP	663470	30
22.5 x 8.25	AH22501-10M	Machined (Valve stem installed)	10	6.63"	0.984"	10 - 285.75mm	53	TR544D	8000 - 130	41644/42644SP	883677/Ultra7	40/45
	AH22501-10P	Polish Both Sides (Valve stem installed)								41644/42644XP	88367X/UltraX (1, 2, or 3)	40/45
	AH22503-10M	Machined (Valve stem installed)	10 (32.5 mm)							28632SP	883610	54
	AH22503-10P	Polish Both Sides (Valve stem installed)	10 (32.5 mm)							28632XP	883613	54
22.5 x 8.25	AH22502-10P	Polish Both Sides (Valve stem installed)	10	6.54"	0.83"	10 - 335mm	51	70MS-7	8040-130	40014SP	886513	53
22.5 x 9.00	AH22504-10P	Polish Both Sides (non-stock)	10	6.91"	0.91"	10 - 285.75mm	63	70MS-7	1000 - 130	41730XP	894653	58
22.5 x 14	AH22514-10M	Machined (Valve stem installed)	10	2.00"	1.00"	10 - 285.75mm	72	TR543E	12800 - 130	42142SP	84U627	55
	AH22514-10P	Polish Both Sides (Valve stem installed)	10	2.00"	1.00"	10 - 285.75mm	72	TR543E	12800 - 130	42142XP	84U622	55
24.5 x 8.25	AH24501-10M	Machined (Valve stem installed)	10	6.61"	.945"	10 - 285.75mm	62	TR544D	7800 - 130	41362SP	98U637	54
	AH24501-10P	Polish Both Sides (Valve stem installed)	10	6.61"	.945"	10 - 285.75mm	62	TR544D	7800 - 130	41362XP	98U63X (1,2)	54

ALUMINUM STUD-PILOTED 15° TUBELESS WHEELS

Wheel Size (Dia. x Width)	KIC Part Number	Polish Option	Hand Holes	Wheel Offset	Disc Thickness	Bolt Hole (#, Diameter)	Weight (lbs.)	Valve Stem	Max Load Rating (lbs.) - (psi)	Accuride Part Number	Alcoa Part Number	Accuride Weight (lbs.)
22.5 X 8.25	AS22501-10M	Machined (Valve stem installed)	10	6.63"	0.984"	10 - 11.25"	53	TR544D	8000 - 130	28615SP	883117	54
22.5 x 8.25	AS24501-10M	Machined (Valve stem installed)	10	6.61"	0.945"	10 - 11.25"	62	TR544D	7800 - 130	27599SP	983127	62

